

# CATR



## Unique Features

Senator air compressors offer an excellent value for money choice with a selection of electric models in the most popular sizes. The Senator range includes 240 Volt units for domestic and trade use, and larger 415 Volt units that are ideal for industrial applications. Designed and built for Australian conditions, Senator air compressors have a proven reputation for quality and reliability at affordable prices.

- Twin or triple cylinder compressor pump with cast iron crankcase and cylinders.
- Alloy cylinder heads fitted with high efficiency reed valves.
- Genuine Teco steel frame, compressor duty motor on 240 Volt models.
- Totally enclosed fan cooled (TEFC), cast iron frame electric motor on 415 Volt models.
- Fully automatic on-off motor control and built-in overload protection.
- Large air receiver tank certified to Australian Standard AS 1210 and protected by a 3-stage corrosion resistant, metallic paint finish.
- Sturdy all-metal, fully enclosed V-belt drive guard.
- 240 Volt models fitted with 2 wheels and removable handle for ease of portability.
- 415 Volt models mounted on pallet feet for safe forklift handling and stable operation.
- Compliant with Australian Workplace Health and Safety Regulations.
- 1-year parts and factory labour warranty. Genuine spare parts available.



## Specifications

### Senator Air Compressors

Model	Pump Displacement		Free Air Delivery		No. of Cyl.	Bore	Stroke	Pump Speed	Electric Motor				Tank Volume	Noise @ 1 m	Outlet Size	Weight	Dimensions (cm)		
	cfm	L/min	cfm	L/min					Qty	mm	mm	rpm					hp	kW	Volts
P13	8.8	249	5.8	165	2	51	46	1,327	2.2	1.65	240	9	60	80	1/4"	76	108	44	76
P17	13.8	389	8.9	253	3	51	48	1,323	3	2.2	240	12.5	60	81	1/4"	84	108	44	79
Z25	23.0	651	15.5	440	2	80	60	1,080	5.5	4	415	7.4	120	77	1/2"	166	135	49	92
Z35	35.2	995	23.8	672	3	80	60	1,100	7.5	5.5	415	10.1	170	81	3/4"	222	143	51	108
Z50	50.1	1,417	38.4	1,087	3	90	75	990	10	7.5	415	13.6	250	84	3/4"	284	173	55	118

- The operating pressure range is factory preset at 85 to 115 psi (586 to 793 kPa), but can be adjusted upwards by approximately 10 psi (69 kPa) for special applications.
- Performance ratings are determined in accordance with Australian Standard AS 4637-2006.
- Filter/regulators are not supplied as standard, but can be purchased separately.
- Specifications are subject to change without notice.



Your local authorized Senator dealer:

**CATR**

174 Musgrave Road, COOPERS PLAINS Q 4108

Call us Toll Free on **1800 248 842**

P >> 07 3275 1822

F >> 07 3274 1069

E >> sales@catr.com.au